

Tile Movement Joint NMJ-S is manufactured using 1.5mm side plate of Brass, Stainless Steel or Aluminum bonded firmly to a rubber insert of 7mm. The side plates range from 15mm onwards to maximum of 100mm in height and can be specially ordered for a greater thickness for heavy duty applications. Rubber inserts are available in 10 standard colours. All profiles are fabricated for a cut length of 2.44mtr or any other required length less than 2.44mtr.

APPLICATIONS


MOVEMENT JOINTS

Type	H		W		L			
	(mm)	(in)	(mm)	(in)	(m)	(in)	(m)	(in)
NMJ-2L10	10	3/8	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"
NMJ-2L12.5	12.5	1/2	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"
NMJ-2L15	15	9/16	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"
NMJ-2L 20	20	3/4	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"
NMJ-2L 25	25	1	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"
NMJ-2L 30	30	1-3/16	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"
NMJ-2L 50	50	2	10	3/8	2.5	8' 2-1/2"	2.7	8' 10-1/4"

Note:

- Other sizes / shapes are available upon request.

STANDARD COLORS



Milky White



Alabaster



Light Beige



Linen



Sandstone



Light Smoke



Earth



Light Grey



Pewter



Black

