

SEISMIC EXPANSION JOINT

FLOOR TO FLOOR

100 - 400 mm Expansion Gap


Features

Surface	Aluminium Strips Sealant
---------	-----------------------------

System Options

Gap width(s)	100 - 400 mm
Height(s)	68 mm
Metal type(s)	Aluminium 6063, T6
Seal Color(s)	Sealant Colors
Waterproofing	Moisture barrier



Type	Joint Width	Pan Width	Total Width	Visible Width	Installation Height	Thermal Movement	Seismic Movement	Load Capacity
	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	[mm]	[mm]	
NFSJ 100	100	205	313	22	68	40 (+20-20)	140 (+50-90)	Pedestrian
NFSJ 150	150	255	363	22	68	40 (+20-20)	190 (+50-140)	Pedestrian
NFSJ 200	200	305	413	22	68	40 (+20-20)	240 (+50-190)	Pedestrian
NFSJ 250	250	355	463	22	68	40 (+20-20)	290 (+50-240)	Pedestrian
NFSJ 300	300	405	513	22	68	40 (+20-20)	340 (+50-290)	Pedestrian
NFSJ 400	400	505	613	22	68	40 (+20-20)	440 (+50-390)	Pedestrian

