

NFSJ-CS

SEISMIC EXPANSION JOINT

FLOOR TO WALL

100-400 mm Expansion Gap


Features

Surface	Aluminium Strips Sealant
---------	-----------------------------

System Options

Gap width(s)	100-400 mm
Height(s)	68 mm
Metal type(s)	Aluminium 6063, T6
Seal Color(s)	Sealant Colors
Waterproofing	Moisture barrier



Type	Joint Width	Pan Width	Total Width	Visible Width	Installation Height	Thermal Movement	Seismic Movement	Load Capacity
	A	B	C	D				
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	
NFSJ 100CS	100	152	206	22	68	40 (+20-20)	90 (+50-40)	Pedestrian
NFSJ 150CS	150	202	256	22	68	40 (+20-20)	150 (+50-100)	Pedestrian
NFSJ 200CS	200	252	306	22	68	40 (+20-20)	200 (+50-150)	Pedestrian
NFSJ 250CS	250	302	356	22	68	40 (+20-20)	250 (+50-200)	Pedestrian
NFSJ 300CS	300	352	406	22	68	40 (+20-20)	300 (+50-250)	Pedestrian
NFSJ 400CS	400	452	506	22	68	40 (+20-20)	400 (+50-350)	Pedestrian

