

UFSJ-C

SEISMIC EXPANSION JOINT

FLOOR TO WALL

100 - 400 mm Expansion Joint Width

Features

Surface	Aluminium Strips Rubber Seal Floor Finish
---------	---

System Options

Joint width(s)	100 - 400 mm
Height(s)	51 mm
Metal type(s)	Aluminium 6063, T6
Seal Color(s)	Black, Grey, Beige, White and Brown
Waterproofing	Moisture barrier



Type	Joint Width	Pan Width	Visible Width	Visible Width	Total Width	Installation Height	Thermal Movement	Seismic Movement	Load Capacity
	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	[mm]	[mm]	
UFSJ 100C	100	123	45.4	62.3	260.7	51	40 (±20)	125 (+60-65)	Pedestrian
UFSJ 150C	150	173	45.4	62.3	310.7	51	40 (±20)	175 (+60-115)	Pedestrian
UFSJ 200C	200	223	45.4	62.3	360.7	51	40 (±20)	225 (+60-165)	Pedestrian
UFSJ 250C	250	273	45.4	62.3	410.7	51	40 (±20)	275 (+60-215)	Pedestrian
UFSJ 300C	300	323	45.4	62.3	460.7	51	40 (±20)	325 (+60-265)	Pedestrian
UFSJ 400C	400	423	45.4	62.3	560.7	51	40 (±20)	425 (+60-365)	Pedestrian

