

# UFSJ-X

## SEISMIC EXPANSION JOINT

### FLOOR TO FLOOR

100-140 mm Expansion Gap

#### Features

Surface	Aluminium Strips Rubber Seal Floor Finish
---------	---

#### System Options

Gap width(s)	100 - 400 mm
Height(s)	160 mm
Metal type(s)	Aluminium 6063, T6
Seal Color(s)	Black, Grey, Beige, White and Brown
Waterproofing	Moisture barrier



Type	Joint Width A [mm]	Pan Width B [mm]	Total Width C [mm]	Visible Width D [mm]	Installation Height E [mm]	Thermal Movement [mm]	Seismic Movement [mm]	Load Capacity
UFSJ 100X	100	267	505	64	160	50 (±25)	175 (+100-75)	UPTO2500
UFSJ 150X	150	317	555	64	160	50 (±25)	200 (+100-100)	UPTO2500
UFSJ 200X	200	367	605	64	160	50 (±25)	250 (+100-150)	UPTO2500
UFSJ 250X	250	417	655	64	160	50 (±25)	300 (+100-200)	UPTO2500
UFSJ 300X	300	467	705	64	160	50 (±25)	350 (+100-250)	UPTO2500
UFSJ 400X	400	567	805	64	160	50 (±25)	450 (+100-350)	UPTO2500

