

UFSJ-XC

SEISMIC EXPANSION JOINT

FLOOR TO WALL

100-140 mm Expansion Gap

Features

Surface	Aluminium Strips Rubber Seal Floor Finish
---------	---

System Options

Gap width(s)	100 - 400 mm
Height(s)	160 mm
Metal type(s)	Aluminium 6063, T6
Seal Color(s)	Black, Grey, Beige, White and Brown
Waterproofing	Moisture barrier



Type	Joint Width	Pan Width	Total Width	Visible Width	Visible Width	Installation Height	Thermal Movement	Seismic Movement	Load Capacity
	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	[mm]	[mm]	
UFSJ 100XC	100	138	46	64	303	160	40 (±20)	115 (+50-65)	UPTO 2500
UFSJ 150XC	150	188	46	64	353	160	40 (±20)	165 (+50-115)	UPTO 2500
UFSJ 200XC	200	238	46	64	403	160	40 (±20)	215 (+50-165)	UPTO 2500
UFSJ 250XC	250	288	46	64	453	160	40 (±20)	265 (+50-215)	UPTO 2500
UFSJ 300XC	300	338	46	64	503	160	40 (±20)	315 (+50-265)	UPTO 2500
UFSJ 400XC	400	438	46	64	603	160	40 (±20)	415 (+50-365)	UPTO 2500

