

SEISMIC EXPANSION JOINT

FLOOR TO FLOOR

100 - 400 mm Expansion Joint Width


Features

Surface	Aluminium Strips Rubber Seal Floor Finish
---------	---

System Options

Joint width(s)	100 - 400 mm
Height(s)	51 mm
Metal type(s)	Aluminium 6063, T6
Seal Color(s)	Black, Grey, Beige, White and Brown
Waterproofing	Moisture barrier



Type	Joint Width A [mm]	Pan Width B [mm]	Total Width C [mm]	Visible Width D [mm]	Installation Height E [mm]	Total Movement [mm]	Seismic Movement [mm]	Load Capacity 
UFSJ 100	100	230	414	62.3	51	50 (±25)	190 (+140-50)	Pedestrian
UFSJ 150	150	280	464	62.3	51	50 (±25)	240 (+140-100)	Pedestrian
UFSJ 200	200	330	514	62.3	51	50 (±25)	290 (+140-150)	Pedestrian
UFSJ 250	250	380	564	62.3	51	50 (±25)	340 (+140-200)	Pedestrian
UFSJ 300	300	430	614	62.3	51	50 (±25)	390 (+140-250)	Pedestrian
UFSJ 400	400	530	714	62.3	51	50 (±25)	490 (+140-350)	Pedestrian

