

UWSJ-C

SEISMIC EXPANSION JOINT

WALL TO CORNER

100 - 400 mm Expansion Joint Width

Features

| | |
|---------|---|
| Surface | Aluminium Strip Rubber Seal Wall Finish |
|---------|---|

System Options

| | |
|----------------|-------------------------------------|
| Joint width(s) | 100 - 400 mm |
| Height(s) | 18 mm |
| Metal type(s) | Aluminium 6063, T6 |
| Seal Color(s) | Black, Grey, Beige, White and Brown |
| Waterproofing | Moisture barrier |



| Type | Joint Width | Pan Width | Visible Width | Visible Width | Total Width | Installation Height | Thermal Movement | Seismic Movement |
|-----------|-------------|-----------|---------------|---------------|-------------|---------------------|------------------|------------------|
| | A [mm] | B [mm] | C [mm] | D [mm] | E [mm] | F [mm] | | |
| UWSJ 100C | 100 | 123 | 45.4 | 62.3 | 260.7 | 18 | 40(±20) | 125(+60-65) |
| UWSJ 150C | 150 | 173 | 45.4 | 62.3 | 310.7 | 18 | 40(±20) | 175(+60-115) |
| UWSJ 200C | 200 | 223 | 45.4 | 62.3 | 360.7 | 18 | 40(±20) | 225(+60-165) |
| UWSJ 250C | 250 | 273 | 45.4 | 62.3 | 410.7 | 18 | 40(±20) | 275(+60-215) |
| UWSJ 300C | 300 | 323 | 45.4 | 62.3 | 460.7 | 18 | 40(±20) | 325(+60-265) |
| UWSJ 400C | 400 | 423 | 45.4 | 62.3 | 560.7 | 18 | 40(±20) | 425(+60-365) |

